

Specifications

Fail Locked **3108**
Fail Unlocked **3308**



WORKING TOGETHER WITH
SERVOCELL

Specifications	
Insert Dimensions with faceplate	1-3/8"D x 8-1/4"H x 1"W (35.0mm D x 209.6mm H x 25.4mm W)
Strike Plate Dimensions with Magnet	1/4"D x 3-5/8"H x 1"W (6.5mm D x 91.7mm H x 25.4mm W)
Bolt Dimensions	1/2" Diameter x 9/16" throw (12.7mm Diameter x 14.5mm throw)
Operating Voltage	12 to 24 VDC
Mode of Operation	Fail Unlocked 3308 or Fail Locked 3108
DSS Output	COM, NO, NC Door Status Sensor, Max 0.2AMP @ 3VDC
Current Consumption	In Rush: 1.15A Normal: 0.25A
Operating Temperature	14 to 104°F (-10 to 40°C)
LED	Purple Wire: COM Blue Wire: RED LED Orange Wire: GREEN LED
Request to Exit Input	NO, momentary contact. Bolt will remain retracted as long as Brown Wire and Yellow Wire are contacted
Relock Time Delay	0, 3, 6, or 10 sec

Bi-Color LED Status	
Extend Successfully	Green blinks every 5 seconds
Wait for Extend	Red blinks fast
Delay Period	Red blinks slowly
Wait for Delay Start	Red on (B Setting only)
Bolt Remains Retracted	Red/Green blinks alternatively

Sounder Status	
Extend Successfully	Beep! Beep!.
Extend Fail	Beep!...Beep! 10 Seconds
Retract Successfully	Beep!

NOTE: Not to scale. Specifications are subject to change without notice.

